

HEROLAK SANTEX BINDER

Product Description	It is an acrylic based special primer
Product Code	752,30,830
Field of Application	on all kinds of plastered, white washed, concrete brick, AAC walls, before initial painting or puttying is applied as primer. Solid matter is 50 %. Depending on dilution and absorption property of the wall, with 1 kg Herolak Santex Binder 30-45 m ² is covered. For high absorbent surfaces, small amount of dilution should be preferred. If the absorption capacity is low, then it can be diluted by 6 times.
Properties	It penetrates the raw wall very well. Fixes and secures the wall surface to a few mm depth. Reduces the consumption of paint to be applied to the wall. Increases the strength of the paint. Solvent-free, non-flammable.
Drying time	2 hours
Thinner	Water
Method of Application	The surface of application should be cleaned. Herolak Santex Binder diluted as given above, should be applied by roller as one cross coat, and care should be taken to avoid film formation. The equipment used should be cleaned with water.
Remarks	Should be stored in close packs without being exposed to direct sunlight. The ambient temperature while storage should be between 5 °C – 35 °C. Keep packs closed when not in use. Preserve against freezing. It should not be consumed under +5°C

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and it does not represent any guarantee of the properties of the product. Herkim Polimer Kimya San. ve Tic. A.Ş. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

AS-03.04/S-TDS-225 REV. NO/ DATE: 00 / 20.09.2018

