

DEKOSEN UVF TRANSPARENT VARNİSH

Product Description	Synthetic resin based, one component, protective top coat varnish series used for exterior facades. It is a varnish that is used in impregnated and moisture-proof facades, elastic, supported by UV filters against sunlight.		
Product Code	735,30,SERIE		
Color	Transparent		
Properties	It can be used in all types of joinery, pergolas, balconies, fences and garden furniture in outdoor areas.		
Solid Content	40 ± 1%		
Density	1,00 ± 0,05 g/ml		
Thinning Ratio	For brush application; With Dekosen Synthetic Thinner (908,01,800) %5 For spray application; With Dekosen Synthetic Thinner (908,01,800) %15 – 20		
Mixture Ratio	-		
Dry Time	Dust dry	30 – 40 min	
	Touch dry	2 – 3 hours	
Pot life @20 °C	-		
Application Viscosity @20 °C, DINCUP #4	15 – 16 s		
Coverage	120 – 150 g/m ² (for 50 – 60 micron dry film thickness)		
Application	Two cross plies are applied to the colored or raw surface with a brush or spray gun intermittently and left to dry. If necessary, use Dekosen Synthetic Thinner or Impregnated Varnish for thinning.		
Remarks	Store in dry and cool area and keep in closed packages. Keep packages closed when not in use. Keep away from sources of ignition- No smoking. Use only in well -ventilated area. Mix before use.		

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and it does not represent any guarantee of the properties of the product. Herkim Polimer Kimya San. ve Tic. A.Ş. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

AS-03.04/S-TDS-48 REV. NO/ DATE: 00 / 03.03.2016

HERKİM POLİMER KİMYA SAN. ve TİC. A.Ş.

A.O.S.B. 10004 Sokak No:4 P.K. 39 B.Çiğli/İZMİR • Tel : (0232) 376 72 41 (Pbx) • Fax : (0232) 376 72 40

İç Anadolu Bölge Müdürlüğü : Yağız Sk. No:14/B Siteler/ANKARA • Tel : (0312) 351 50 32 • Fax : (0312) 351 50 33

Akdeniz Bölge Müdürlüğü : Şafak Mah. 4259 Sk. No:14 ANTALYA • Tel : (0242) 221 21 15 • Fax : (0242) 221 24 77

www.herkim.com • e-mail: info@herkim.com

