

IMPREGNATED CLEAR VARNISH

Product Description It is a varnish that protects wood from destruction by fungi and insects due to its special structure and protects it from external conditions. Impregnated Varnish is colorless, but it is also possible to make Colored Impregnated Varnish if desired.

Product Code 745,30,830

Color Transparent

Properties It is used as the first surface protector on massive surfaces such as outdoor joinery, pergolas, balcony scare, fence etc.

Solid Content -

Density 0,85 ± 0,05 g/ml

Thinning Ratio -

Weight

Mixture Ratio -

Dry Time Dust dry 20 - 30 min

Touch dry 2 - 3 hours

Pot life -
@20 °C

Application Viscosity Package viscosity
@20 °C, DINCUP #4

Coverage 20 - 25 L. impregnated varnish for 1 m³ wood

Application It is applied by dipping or brush after the wood takes its final form. For dipping application all parts of the object should be in Impregnated Varnish and stay in, depending on the structure of the wood, from 5 to 15 minutes. Impregnated wood should be rested on top of the dipping tank for 3 to 5 minutes for draining. During application 20-25 L of impregnated varnish is required for 1 m³ of wood. One day after impregnation, painting, two days after pasting can be done.

Remarks Store in dry and cool area and keep in closed packages. Keep packages closed when not in use.
Keep away from sources of ignition- No smoking.
Use only in well -ventilated area.
Mix before use.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and it does not represent any guarantee of the properties of the product. Herkim Polimer Kimya San. ve Tic. A.Ş. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

AS-03.04/S-TDS-79 REV. NO/ DATE: 00 / 03.06.2016

